Incremental Linking on HP-UX

Dmitry Mikulin
Hewlett-Packard Company
mikulin@cup.hp.com

Murali Vijayasundaram
Hewlett-Packard Company
vm@cup.hp.com

Loreena Wong
Hewlett-Packard Company
loreena@cup.hp.com

Abstract

The linker is often a time bottleneck in the development of large applications. Traditional linkers process all input files, even if only one or two objects have changed since the previous link. To shorten link time, we have developed an incremental linker for HP-UX which only processes modified files. Users can take advantage of the performance gains without modifying their usage patterns of the existing HP-UX linker since the incremental linker is implemented on top of the regular 64-bit linker. In addition to the tasks of the normal linker, the incremental linker must save extra information about input files, symbols and relocations, allow for the expansion of existing files and addition of new ones by allocating padding spaces in the output file and use this information to perform in-place updates. The results of several different design considerations and tradeoffs are materialized in link-time performance gains of up to thirteen times that of a normal link for large applications.

1. Introduction

1.1 Motivation behind incremental linking

In recent years application sizes have grown dramatically. This increase has been enabled by significant advances in software development tools such as object-oriented languages which shorten development cycles and allow smaller groups of developers to produce very complex applications with hundreds of thousands or even millions of lines of code. Understandably, these applications take longer to compile and link. This increase becomes most obvious during application debugging when multiple edit-compile-link-debug cycles must be performed in a short period of time. Most changes involve only a small portion of an application source base, typically one or two modules. The problem of long compile times is partially solved by 'make' utilities that recompile only modified source files. Unfortunately there is no easy solution for traditional linkers—they still need to process all object files and libraries to resolve cross-module references and assign addresses to all symbols. The linker becomes a bottleneck that significantly affects a developer's productivity.

The only way to shorten link time, apart from making algorithmic improvements in the linker itself, is to reduce the size of input processed by the linker. Since only a few object files are typically modified before a link is performed, it is possible to reduce the input size by only processing modified objects and replacing their contribution to the output files in place. This fact is the motivation behind the incremental linker.

An incremental linker should process only those input files that have been modified since the last time a link was performed. With meticulous planning and saving of necessary data, all other input files that have not changed should not need to be reprocessed.

1.2 Related work

Despite the great importance of fast link times and the fact that several production systems have implemented incremental linkers (IBM mainframes had incremental linking capabilities since the 1960s; Sun Microsystems offers this functionality which can be optionally enabled on their Solaris systems; Microsoft C/C++ Development Studio has it enabled by default in debug links), very little has been written on the subject.

An academic paper by Quong and Linton [1] provided us with valuable analysis of padding space allocation and reuse. It also contained important performance data for programs of various sizes. Even though the authors chose a different approach in their implementation (a memory resident component which maintains state information about the incremental linker), the paper gave us insight into usage patterns as well as performance and implementation trade-offs.

A paper by Hoffman and Curwen [2] described an alternative way of solving the problem of long link times based on dynamic linking. Object files comprising the application are grouped into shared libraries which are smaller and therefore can be linked faster. Source changes cause only enclosing libraries to be rebuilt. This approach primarily addresses linking simple applications and will fail in cases with name collisions between shared and archive libraries. Dynamic linking is not always supported (e.g. in embedded systems) and may require significant build process changes which makes the scheme not very practical.

1.3 The HP-UX standard linker

The main job of the linker is to merge several relocatable object files into a single load module (a shared library or an executable program file). In doing this merge, the linker must resolve references across the input objects, layout and assign addresses to the resulting load module. In addition, the linker must be able to handle references to symbols defined outside the current load module. For example, if several object files are linked together with a shared library, the referenced code in the shared library is not copied into the output file. Instead, the linker creates dynamic symbols for these types of references and places information in the output file so that when the proper shared library is brought in at runtime by the dynamic loader, the symbol reference can be bound based on the load address of the program file and shared library. Dynamic symbols are also created for all global symbols which may be referenced outside the load module.

Another key task of the linker is to perform symbol resolution—the process of matching references to the definition of a symbol. If a reference can be bound to a definition within the load module, the linker can simply replace the reference with the address of the symbol. If the reference can not be bound to a definition within the load module, the linker will create a dynamic relocation. The dynamic relocations will be processed by the dynamic loader at runtime.

The linker also supports a –r option to merge multiple object files into a single relocatable object. When the –r option is specified, the linker will retain the symbol and relocation information in the output file, making it suitable for subsequent re-linking.

2. Overview of incremental linking

Incremental linking support on HP-UX is implemented as part of the standard 64-bit linker. Aside from a few exceptions, the vast majority of linker options and functionality is available with incremental linking as well, enabling users to take advantage of the performance gains without sacrificing linker functionality when building shared libraries and executables.

The 64-bit linker now has three operating modes:

- Normal link mode: Normal linker operation. This is the default mode.
- Initial incremental link mode: This mode is entered when the +ild option is specified and the output load module (executable or shared library) does not exist or the output load module is not an incrementally linked executable. In this mode, the linker will create an output load module that is suitable for incremental linking.
- Incremental link mode: This mode is entered when the +ild options is specified and the incrementally linked output load module exists. In this mode, the linker will make incremental updates to the output load module. It is in this mode that the great performance gains can be realized.

This paper focuses only on the latter two modes.

In initial incremental links, the linker processes all input object files and libraries the same as it does for normal links. In addition to this basic functionality, the incremental linker must do additional work to enable subsequent incremental links. The linker must store extra information about the input files processed, all global symbols, as well as relocations. Also, the incremental linker must allocate proper padding space for text, data, bss, and other sections in the output file in order to allow room for future expansion from additional input files, definitions, references, etc. Because of this added functionality required for initial incremental links, the time spent in initial links is slightly higher than that of a normal link.

Once all the proper information has been stored in an initial incremental link, subsequent incremental links can be performed. The linker uses timestamps on individual input files to determine which files have changed and only reprocesses modified files during incremental links. The linker uses saved relocation information to patch the symbolic references in the rest of the output file. These tasks are described in greater detail in the rest of this paper.

The incremental linker is intended for use by programmers during developmental stages only, and should not be used for release builds of products. Because the incremental linker pads sections for future expansion, programs are bloated in size and contain information not necessary for execution of the program. In addition, the incremental linker is incompatible with most compile- and link-time optimization techniques and thus cannot produce optimized executables. The incremental linker, however, is an excellent timesaving tool for use during development when programmers are constantly adding and modifying small portions of code and rebuilding programs for testing. In addition, incrementally linked programs are still source-level debuggable in the same manner as normally linked executables.

The remainder of this document describes design considerations and implementation details, and performance results of the incremental linker for HP-UX.

3. Command line, file and library processing

Because our incremental linker is implemented as an extension of the regular system linker, practically all options are allowed when building incrementally linked executables and shared libraries. The use of the mapfile option, which allow users to change the layout of the output load module through a mapping file, is also supported, as long as the specified mapfile doesn't change between incremental links; if it does, we fall back to an initial incremental link. The only options incompatible with incremental linking are link time performance and optimization options. Some linker options significantly influence the resulting output module and if added to or removed from the command line, may make the executable difficult or impossible to incrementally update. For this reason, we decided not to allow any command line option changes in incremental links with the exception of tracing and verbose options; these can be freely added, removed or changed since they have no effect on the resulting output file.

In an initial incremental link, file names, types and time stamps for all object files, shared libraries, archive libraries and their processed members are saved in the output file. In subsequent incremental links, this information is used to detect which files need to be reprocessed. For object files, the logic is simple: if a file's time stamp has changed, that file needs to be reprocessed.

If an archive library is modified, we need to check each individual member processed in previous links for time stamp changes and reprocess only the ones that were actually modified. In some cases, we may need to reprocess an archive library even if the archive itself was not modified. If any of the modified object files introduces a new unresolved symbol reference, we need to scan archive library symbol tables and extract members that define that symbol. However, contributions of archive members are never removed from the output file, even if there are no more references to any of the symbols defined in those members.

Since symbols from shared libraries are not propagated into the output file, we do not reprocess shared libraries during incremental links. Instead, it is the dynamic loader's responsibility to catch unresolved symbols at runtime.

4. Padding and reuse of space

The incremental linker re-links programs by inserting modified object code into the existing output file. During the initial incremental link various output file sections such as text, data, bss etc., are padded with additional space for future expansion. The output file data structures like symbol table, section table and linkage tables are also padded with additional space.

During incremental links, the linker will vacate the space occupied by modified object files. The vacated space in the output file will be reused when the contents of the modified object files are copied over to the output file. The incremental linker always tries to fit the modified object file's contributions into their previous location. After several incremental links, the padding space may become exhausted. When this occurs, the incremental linker will fall back to performing a full initial incremental link during which additional padding space will be allocated.

4.1 Padding space allocation

The incremental linker allocates two kinds of padding spaces:

- File specific padding space. Each section in the output file consists of contributions from all object files. The Figure 1 shows the layout of an output section created during normal link. The incremental linker allocates a padding space after contributions form each object file. These file specific padding spaces are allocated to allow for possible growth in the object file's contributions. Figure 2 shows the layout of an output section with file specific padding.
- Generic padding space. During incremental links new object files may be added to the link. To accommodate contributions from new object files, a large padding area (as shown in Figure 2) is allocated at the end of each output section.



Figure 1. Layout of an output section by the normal linker