

# Network Shells

Michael Smith




Image: <https://commons.wikimedia.org/wiki/File:Network-connections.png>

```
chealer@vinci:/usr/share/doc/bash$ export LC_ALL=C
chealer@vinci:/usr/share/doc/bash$ cd ~chealer/
chealer@vinci:~$ ls
Cloutier Ido      Musique logs      skolo sources
Desktop   Mes images boston  ncix.png smb4k vieux
chealer@vinci:~$ #Why is there color when calling ls without arguments?
chealer@vinci:~$ which ls
/bin/ls
chealer@vinci:~$ $(!!)
$(which ls)
Cloutier Ido      Musique logs      skolo sources
Desktop   Mes images boston  ncix.png smb4k vieux
chealer@vinci:~$ type ls #"ls" doesn't just run /bin/ls
ls is aliased to `ls --color=auto'
chealer@vinci:~$ echo $PS1
${debian_chroot:+($debian_chroot)}\u@\h:\w\$
chealer@vinci:~$ sh
sh-3.1$ echo $PS1
\s-\v\$
sh-3.1$ echo $BASH_VERSION
3.1.17(1)-release
sh-3.1$ ls
Cloutier Ido      Musique logs      skolo sources
Desktop   Mes images boston  ncix.png smb4k vieux
sh-3.1$ echo ${SHELLOPTS} # ls isn't an alias in POSIX mode
braceexpand:emacs:hashall:histexpand:history:interactive-comments:monitor:posix
sh-3.1$ kill
kill: usage: kill [-s sigspec | -n signum | -sigspec] pid | jobspec ... or kill
-l [sigspec]
sh-3.1$ /bin/kill &> killerror # collect stdout and stderr of $ /bin/kill; in ki
llerror
sh-3.1$ wc -l !$
wc -l killerror
7 killerror
sh-3.1$ type kill # kill doesn't just run /bin/kill, even in POSIX mode.
kill is a shell builtin
sh-3.1$ !$ -n 9 $$ # OK, kill self
kill -n 9 $$ # OK, kill self
Killed
chealer@vinci:~$
```

# What does a Shell give us?

- A REPL
- Repeatability
- Direct access to system operations
- User-focused design
- Hierarchical context & sense of place

Image: [https://upload.wikimedia.org/wikipedia/commons/8/84/Bash\\_demo.png](https://upload.wikimedia.org/wikipedia/commons/8/84/Bash_demo.png)

```
chealer@vinci:/usr/share/doc/bash$ export LC_ALL=C
chealer@vinci:/usr/share/doc/bash$ cd ~chealer/
chealer@vinci:~$ ls
Cloutier Ido      Musique logs      skolo sources
Desktop   Mes images boston  ncix.png smb4k vieux
chealer@vinci:~$ #Why is there color when calling ls without arguments?
chealer@vinci:~$ which ls
/bin/ls
chealer@vinci:~$ $(!!)
$(which ls)
Cloutier Ido      Musique logs      skolo sources
Desktop   Mes images boston  ncix.png smb4k vieux
chealer@vinci:~$ type ls #"ls" doesn't just run /bin/ls
ls is aliased to `ls --color=auto'
chealer@vinci:~$ echo $PS1
${debian_chroot:+($debian_chroot)}\u@\h:\w\$
chealer@vinci:~$ sh
sh-3.1$ echo $PS1
\s-\v\$
sh-3.1$ echo $BASH_VERSION
3.1.17(1)-release
sh-3.1$ ls
Cloutier Ido      Musique logs      skolo sources
Desktop   Mes images boston  ncix.png smb4k vieux
sh-3.1$ echo ${SHELLOPTS} # ls isn't an alias in POSIX mode
braceexpand:emacs:hashall:histexpand:history:interactive-comments:monitor:posix
sh-3.1$ kill
kill: usage: kill [-s sigspec | -n signum | -sigspec] pid | jobspec ... or kill
-l [sigspec]
sh-3.1$ /bin/kill &> killerror # collect stdout and stderr of $ /bin/kill; in ki
llerror
sh-3.1$ wc -l !$
wc -l killerror
7 killerror
sh-3.1$ type kill # kill doesn't just run /bin/kill, even in POSIX mode.
kill is a shell builtin
sh-3.1$ !$ -n 9 $$ # OK, kill self
kill -n 9 $$ # OK, kill self
Killed
chealer@vinci:~$
```

# What does a Shell give us?

- A REPL
- Repeatability
- Direct access to system operations
- User-focused design
- Hierarchical context & sense of place

Image: [https://upload.wikimedia.org/wikipedia/commons/8/84/Bash\\_demo.png](https://upload.wikimedia.org/wikipedia/commons/8/84/Bash_demo.png)

# Management at a distance (netsh)

---


Netsh: Configure DHCP servers with

```
netsh -r RemoteMachine -u domain\username
```

```
[RemoteMachine] netsh>interface
```

```
[RemoteMachine] netsh interface>ipv6
```

```
[RemoteMachine] netsh interface ipv6>show interfaces
```



Reference: <https://docs.microsoft.com/en-us/windows-server/networking/technologies/netsh/netsh-contexts>

# Management at a distance (netsh)

---

Netsh: Configure DHCP servers with

```
netsh [RemoteMachine] location noteMachine -> domain\username
```

```
[RemoteMachine] netsh [RemoteMachine] context ace
```

```
[RemoteMachine] netsh interface>ipv6
```

Hierarchical  
context

Simpler  
commands

```
[RemoteMachine] netsh interface ipv6>show interfaces
```

# Management at a distance (WSMan)

----

WSMan (in Powershell): Manage Windows remotely with

```
Set-Location -Path WSMan:\SERVER01
```

```
Get-ChildItem -Path .
```

```
Set-Item Client\TrustedHosts *.domain2.com -Concatenate
```

# Management at a distance (other examples)

----

[github.com/fishi0x01/vsh](https://github.com/fishi0x01/vsh) - for manipulating Vault secrets

[code.vmware.com/web/tool/11.4.0/vmware-powercli](https://code.vmware.com/web/tool/11.4.0/vmware-powercli) - for managing everything VMWare in PowerShell

[github.com/vmware/rvc](https://github.com/vmware/rvc) - a console for vSphere

[metacpan.org/pod/distribution/ldapsh/ldapsh](https://metacpan.org/pod/distribution/ldapsh/ldapsh) - a shell for editing LDAP

# Interlude: PowerShell Providers

---

`Get-Item` alias:

`Get-ChildItem`

`HKLM:\SOFTWARE\`

`Set-Location cert:`

`Get-ChildItem`

Reference:

[https://docs.microsoft.com/en-us/powershell/module/microsoft.powershell.core/about/about\\_providers](https://docs.microsoft.com/en-us/powershell/module/microsoft.powershell.core/about/about_providers)


Provider	Drive	Data store
Alias	Alias:	PowerShell aliases
Certificate	Cert:	x509 certificates for digital signatures
Environment	Env:	Windows environment variables
FileSystem	(*)	File system drives, directories, and files
Function	Function:	PowerShell functions
Registry	HKLM:, HKCU:	Windows registry
Variable	Variable:	PowerShell variables
WSMan	WSMan:	WS-Management configuration information

# Hide the network (NFS, SSHFS, GlusterFS)

Image: from Hackers (1995)

<https://www.slashfilm.com/hackers-oral-history/>


## Userspace



## Kernel

### Interlude: Filesystem in Userspace (FUSE)

VFS



# Remote execution in your shell (NSH by BMC)

----

```
nsh @% cd //host1
nsh host1% uname -a
host1
nsh host1% tail /var/log/messages
Oct 24 17:21:43 localhost liblogging-stdlog: [origin
software="rsyslogd" swVersion="8.24.0" x-pid="486"
x-info="http://www.rsyslog.com"] start
...
...
```

# Remote execution in your shell (NSH by BMC)

----

```
nsh @% cd //host1
```

```
nsh host1% tail /var/log/messages
```

```
nsh host1% cp //host2/home/myuser/some_archive.tar /tmp/
```

# Remote execution in your shell (NSH by BMC)

----

```
nsh host1% cp //host2/home/myuser/some_archive.tar /tmp/
```

```
nsh host1% cp /tmp/some_archive.tar //@/some/dir
```

```
nsh @% ndf; nps; ntop; nmem; nexec
```

# Remote execution in your shell (Wash)

---

```
wash . > ls  
aws/  
docker/  
gcp/  
kubernetes/
```

```
wash . > ls gcp/Wash/compute  
michael-test-instance  
  
wash . > tree gcp/Wash/storage  
gcp/Wash/storage  
└── some-wash-stuff  
    ├── an\ example\ folder  
    └── static.sh  
    └── reaper.sh
```

# Remote execution in your shell (Wash)

----

```
wash gcp/Wash/compute/a-host > tail fs/var/log/messages
Oct 24 17:21:43 localhost liblogging-stdlog: [origin
software="rsyslogd" swVersion="8.24.0" x-pid="486"
x-info="http://www.rsyslog.com"] start
```

...

```
wash gcp/Wash/compute/a-host > meta .
cpuPlatform: Intel Broadwell
creationTimestamp: "2019-10-24T10:21:33.167-07:00"
```

...

# Remote execution in your shell (Wash)

---

```
wash . > find . -crtime -30d -action exec  
./aws/eso/resources/ec2/instances/wash-test_i-0c64807d0ef65c585  
./gcp/Wash/compute/a-host  
./kubernetes/gke_shared-k8s_us-west1-a_shared-k8s-dev/monitoring/pods/promethe  
us-64c6dfb964-tzmbbr/prometheus  
...  
wash aws/eso > find resources -meta '.Tags[?]' '.Key Team -a  
.Value wash  
./ec2/instances/wash-test_i-0c64807d0ef65c585  
...
```

**Why do we love them?**


**Why do we love them?**

# Reinventing the wheel

Caching

Cross-platform clients

Network resources are often  
not files



# Thank You